
24x10x0.5 DOUBLE ANGLE

REMOVABLE CEILING PROFILES

DESCRIPTION

Pre-lacquered steel W-shaped profile measuring 24x10x10x24 mm and 3 metres in length for constructing removable suspended ceilings. This is a perimeter profile that is used to support the primary and secondary profiles that make up the structure of the false ceilings. Its ends have a 180° anti-cut fold that grants it greater rigidity, thereby increasing its mechanical performance.



24 x 10 x 10 x 24

MATERIAL

Profiles made by shaping a sheet of pre-lacquered steel plus coatings.

Reaction to Fire test at AFITI (UNE-EN 13501-1:2019)

Steel profile test in Afiti, report 4292T21-2 PROFILES. Result: Euroclass A1. Non-combustible product (no contribution to fire), with low quantity and speed of smoke emission and does not produce inflamed droplets or particles.

SUPPLY

ANGLE PROFILE LENGTH	LINEAR METRES X BOX	LINEAR METRES PER PALLET	KILOS X BOX
3 M	45	5940	13

UPDATED VERSION

To view the latest version of this document, scan this QR code.

Version 0
07/01/2024

THU Ceiling Solutions reserves the right to change the content of this document without prior notice. Every effort has been made to ensure that the content of this publication is accurate, but THU Ceiling Solutions accepts no liability for any errors or potentially misleading information. Suggestions regarding the end use or application of the products or working methods are for information purposes only and THU Ceiling Solutions accepts no liability in this regard.

Masía de Monte Alcedo Parcela, 4.3
P.I. Masía Baló, 46394 Ribarroja del Turia, Valencia

Telephone: 96 134 05 44
Fax. 96 166 78 21

info@thu.es
www.thu.es