
TC(NF) CONTINUOUS CEILING


EN 14195 metal profiles

DESCRIPTION

C-shaped galvanised steel profile in 45, 47 and 60 mm widths, variable lengths for the construction of plasterboard false ceilings. It has a knurled underside to make it easier to screw in the boards. Its ends have a 180° anti-cut fold that grants it greater rigidity, thereby increasing its mechanical performance.

DESCRIPTION	TC-45x18	TC-47x17	TC-60x28
Width A	45.00+-0.50	47.00+-0.50	60.00+-0.50
Flange B	18.50+-0.50	17.00+-0.50	28.00+-0.50
Flange C	18.50+-0.50	17.00+-0.50	28.00+-0.50
Nominal thickness	0.60±0.04	0.60±0.04	0.60±0.04
Coating	Z-140	Z-140	Z-140





MATERIAL

Profiles formed by folding (S220GD + Z140) galvanised steel sheets with a thickness of 0.60±0.04 mm (tolerances established in accordance with the UNE-EN 10143 standard), with the supplier's quality certificate.

APPLICATION: for the installation of continuous ceilings using laminated plasterboards

1) Plasterboards

There is a wide variety of plasterboards on the market with excellent thermal and acoustic insulation properties, good fire resistance, easy assembly and ease of handling.

3) **45, 47 and 60 TC and TCT profile battens. Suspension part**

To support the system, 3-metre long galvanised steel battens are used with TC and TCT profiles (for 45, 47 and 60 mm wide models). Failing this, suspension parts can be used. The system is supported by M6 threaded rods.

4) **Mineral fibre blanket**

To ensure satisfactory sound insulation, mineral fibre blankets are placed on top of the plasterboards, with a certain thickness and density, as required.

PROPERTIES

Reaction to Fire

Class A1 (No contribution to Fire), in accordance with UNE/EN 14195:2005, which establishes said classification for construction products made of steel without the need for testing.

Acoustic Absorption and Insulation

Mineral wool fibres of a certain thickness and density are used for the acoustic conditioning of rooms with plasterboard ceilings. For optimal acoustic conditioning, refer to the technical information (thermal and acoustic behaviour) provided by the manufacturer of the plasterboard plates installed with this profile.

Masía de Monte Alcedo Parcela, 4.3
P.I. Masía Baló, 46394 Ribarroja del Turia,
Valencia

Phone. 96 134 05
44 Fax. 96 166 78
21

info@thu.es
www.thu.es

SUPPLY

DESCRIPTION	LENGTH	PALLET lm	PALLET kg	PALLET DIMENSIONS (*) base x height
TC-45x18	3.0 m	2160 m	964 kg	1130x390 mm
TC-45x18	4.5 m	3240 m	1380 kg	1130x390 mm
TC-45x18	5.0 m	3000 m	1300 kg	1130x300 mm
TC-47x17	3.0 m	2160 m	964 kg	1130x390 mm
TC-47x17	4.5 m	3240 m	1380 kg	1130x390 mm
TC-47x17	5.0 m	3000 m	1300 kg	1130x300 mm
TC-60x28	3.0 m	1200 m	729 kg	1130/420 mm
TC-60x28	4.5 m	1800 m	1093 kg	1130x420 mm

*Includes block and board (90 mm)

UPDATED VERSION

To view the latest version of this document, scan this QR code.

Version 0
6 June 2025

THU Ceiling Solutions reserves the right to change the content of this document without prior notice. Every effort has been made to ensure that the content of this publication is accurate, but THU Ceiling Solutions accepts no liability for any errors or potentially misleading information. Suggestions regarding the end use or application of the products or working methods are for information purposes only and THU Ceiling Solutions accepts no liability in this regard.